神州云科
Yunke China

YK SR760xs

Outline

YK SR760xs 2U 2U

(VDI) (VM) (SDS)

Advantages

YK SR760xs 2U

CPU I/O

- 5 ® ® 28 4
  ® ® 32
- 16 DDR5 RDIMM 5200 MT/
- 8 I/O 6 PCIe 1 OCP 3.0
  1 PERC
- 12 3.5 HDD/SSD 16 2.5
  HDD/SSD 8 NVMe

神州云科
Yunke China

YK SR

: , ,

USB

YK SR CNP

I/O

- Cloud Native Application
-
-
-

Live Optics

Live Optics IT

Live Optics

Live Optics

- —

  Live Optics

  “ ”

- — IT Live

  Optics

  Viewer Live Optics

  IO,

  , ,CPU,

OpenManage

OpenManage OpenManage

- HTML5 GUI VMware ESXi Microsoft Hyper-V KVM

  OpenManage

- OpenManage Mobile

  wifi NFC 1

  VNC

- OpenManage Mobile IT

  ,

- APP Android IOS WIFI

- OpenManage Enterprise

  OpenManage Mobile

-

- 8000 8000

- OpenManage Enterprise

- IT

- OpenManage Enterprise

  /

  e H 0 FO ðà BOBHS F l&8OHFS QS B. TH ð ` G2Q penManage Ent p " ise

神州云科
Yunke China

-
-
-
-

IT

YK SR

(MFA)

YK OpenManage™ YK SR

OpenManage Enterprise YKDRAC

YK SR

YK Services

神州云科
Yunke China

Parameters

	• 5 28 4 32
	• 16 DDR5 DIMM 1.5 TB RDIMM 5600 MT/s ECC DDR5 DIMM
	• PERC H965i PERC H755 PERC H755N PERC H355 HBA355i • Boot Optimized Storage Subsystem (BOSS-N1) HWRAID 1 2 x M.2 NVMe SSD USB • HBA RAID HBA355e RAID S160
	• 0 • 8 x 3.5 SAS/SATA (HDD/SSD) 160 TB • 12 x 3.5 SAS/SATA (HDD/SSD) 240 TB • 8 x 2.5 SAS/SATA/NVMe (HDD/SSD) 122.88 TB • 16 x 2.5 SAS/SATA (HDD/SSD) 121.6 TB • 16 x 2.5 (SAS/SATA) + 8 x 2.5 (NVMe)(HDD/SSD) 244.48 TB • 2 x 2.5 SAS/SATA/NVMe (HDD/SSD) 30.72 TB 12 x 3.5 SAS/SATA HDD/SSD

	• 1800 W 200-240 VAC 240 VDC • 1400 W 100-240 VAC 240 VDC • 1400 W 277 VAC HVDC HVDC DC 336V DC • 1100 W 100-240 VAC 240 VDC • 1100 W -(48V — 60V) DC • 800 W 100-240 VAC 240 VDC • 700 W 200-240 VAC 240 VDC • 600 W 100-240 VAC 240 VDC
	•
	• (STD) / (HPR) / (VHP) 6
	• - 86.8 3.41 • - 482 18.97 • - 707.78 27.85 - 721.62 28.4 - • - 28.6 63.0
	• 2U
	• iDRAC9 • iDRAC Service Module • iDRAC Direct • Quick Sync 2

	• Redfish iDRAC RESTful API
OpenManage	• CloudIQ for PowerEdge • OpenManage Enterprise • OpenManage Enterprise Integration for VMware vCenter • OpenManage Integration for Microsoft System Center • OpenManage Integration with Windows Admin Center • OpenManage Power Manager • OpenManage • OpenManage Update Manager
	OpenManage Mobile
OpenManage	• BMC Truesight • Microsoft System Center • OpenManage Integration with ServiceNow • Red Hat Ansible Modules • Terraform • VMware vCenter and vRealize Operations Manager
	• • SED • •

	• • • iDRAC9 Enterprise Datacenter • TPM 2.0 FIPS CC-TCG TPM 2.0 NationZ
NIC	2 x 1 GbE LOM
	1 x OCP 3.0
GPU	2 x 75 W SW LP
	1 iDRAC Direct (Micro-AB USB) 1 USB 2.0 1 VGA 1 x USB 3.0 1 iDRAC 1 USB 2.0 1 USB 3.0 1 VGA 1
PCIe	• CPU 4 PCIe 2 x8 5.0 1 x16 4.0 1 x8 4.0 • CPU 6 PCIe 2 x16 5.0 2 x16 4.0 3 x8 4.0
	Canonical Ubuntu Server LTS Citrix Hypervisor Hyper-V Microsoft Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMWare ESXi

神州云科
Yunke China



DC Yunke Beijing Technology Co., Ltd.

www.yunke-china.com

4006680103

© 2020